Carmel B.K. Engineering LTD. כרמל ב.ק. הנדסה בע"מ
Industrial Paint & Maintenance Products יבוא, יעוץ ושיווק
26 Hamelacha St., Hof Shemen, HAIFA. POST: EGOZ 12 HAIFA 3479230 , Israel , 3479230 חיפה דואר: אגוז 12 חיפה, חוף שמן, 26 רח' המלאכה
www.carmel-eng.co.il ,E-Mail: info@carmel-eng.co.il ,Fax. 15348245467 פקס: ,Tel. 972-4-8620740 טל.

AutoCoat – Acrylic Polyurethane Industrial Finish

Category: Industrial Topcoat

Description

High-quality two-component acrylic polyurethane coating for industrial and general applications.



Key Benefits

✓ Excellent durability and chemical resistance

✓ Suitable for metal, plastic and composites

✓ Non-yellowing finish

✓ Smooth glossy appearance

Technical Data

Parameter	Value
Type	Two-component acrylic polyurethane
Gloss	3–80 GU
DFT	40–60 microns
Drying Time	Touch dry: 2h | Full cure: 5–7 days
Shelf Life	12 months

Typical Applications

- Industrial equipment

- Civilian/military vehicles

- General protective coating

Relevant Standards & Reports

• Internal QC Reports

Contact

Carmel B.K. Engineering Ltd.
Tel: 04-8620740 | Email: office@carmel-eng.co.il
Website: www.carmel-eng.co.il