Carmel B.K. Engineering LTD. כרמל ב.ק. הנדסה בע"מ
Industrial Paint & Maintenance Products יבוא, יעוץ ושיווק
26 Hamelacha St., Hof Shemen, HAIFA. POST: EGOZ 12 HAIFA 3479230 , Israel , 3479230 רח' המלאכה 26, חוף שמן, חיפה. דואר: אגוז 12 חיפה
www.carmel-eng.co.il ,E-Mail: info@carmel-eng.co.il ,Fax. 15348245467 פקס: ,Tel. 972-4-8620740 טל.

Primer Plast

Category: Primer / Acrylic Polyurethane

Description

Two-component acrylic polyurethane primer for Aluminum, plastics.

Key Benefits



✓ Excellent adhesion on MDF, ABS, PVC, Aluminum.

✓ RoHS and REACH compliant

✓ Non-chrome, lead-free pigments

✓ Good outdoor resistance

Technical Data

Parameter	Value
Type	Two-component acrylic polyurethane
DFT	60–80 microns
Gloss	20 GU (60°)
Drying Time	Tack free: 30 min | Full cure: 12–24 h
Shelf Life	Base: 24 months | Hardener: 12 months

Typical Applications

- Wood, MDF, OSB

- PVC, ABS, Polyester

- ABS, PVC, Aluminum

Relevant Standards & Reports

• RoHS, REACH

Contact

Carmel B.K. Engineering Ltd.
Tel: 04-8620740 | Email: office@carmel-eng.co.il
Website: www.carmel-eng.co.il